

HIGHLIGHTS	800	1000
AGILE	<ul style="list-style-type: none"> Sturdy engine and transmission Easy Handling and capabilities Front and rear suspension designed for trail riding 	
ADVENTUROUS	<ul style="list-style-type: none"> Meaningful functionalities and versatility Enhanced comfort with Ergo-Lok cockpit Build your Maverick Trail that fits your needs 	
CONFIDENT	<ul style="list-style-type: none"> Can-Am design and proven fit & finish Enhanced protection More adventure and less maintenance 	
PLATFORM FEATURES	<ul style="list-style-type: none"> 60 in. wide (62 in. with mirrors) 90.6 in. Wheelbase 10 in. of ground clearance Up to 10.5 in. suspension travel 7.6 in. (19.3 cm) wide digital display with keypad SPORT / ECO™ modes Net (instead of doors) RF key DESS with Start / Stop button Mudguard and Mudflap Rear hitch and tow ball 7-pin trailer connexion (12V) LED tail lights with halo glow effect Horn, flashers and position lamps, left/right mirrors, license plate support, hook on front metal bumper, driver seat detector, Low brake fluid sensor 	
SPECIFIC TO DPS T PACKAGE	<ul style="list-style-type: none"> Dynamic Power Steering (DPS™) 12 in. (30.5 cm) aluminum wheels Ergoprint seats with color accents over 60KM/H top speed Open front diff. with Brake Traction Control (BTC) Dynamic Brake Control (ABS + HHC + HDC) Dynamic Traction Control (BTC + DTC) 	
		Dynamic Traction Control (TCS can be switched off)

ENGINES	800	1000
Type	51 hp, Rotax® 799.9 cc, V-twin, liquid cooled, with catalytic converter	75 hp, Rotax® 976 cc, V-twin, liquid cooled, with catalytic converter
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)	
Transmission	Quick Response System (QRS) CVT with high airflow ventilation and Electronic Drive Belt Protection Extra-L / H / N / R / P	
Drive Train	Selectable 2WD / 4WD with Open front diff. with Brake Traction Control (BTC)	
Driving Assistance	Electronic Hill Descent Control SPORT / ECO™ modes	
Power Steering	Dynamic Power Steering (DPS)	
SUSPENSIONS		
Front Suspension	Double A-arm with sway bar / 10 in. (25.4 cm) travel	
Front Shocks	Twin tube gas charged shocks	
Rear Suspension	TTA with sway bar / 10.5 in. (26.7 cm) travel	
Rear Shocks	Twin tube gas charged shocks	
TIRES / WHEELS		
Front Tires	Carlisle ACT 26 x 8 x 12 in. (66 x 20.3 x 30.5 cm)	
Rear Tires	Carlisle ACT 26 x 9 x 12 in. (66 x 22.9 x 30.5 cm)	
Wheels	12 in. (30.5 cm) cast-aluminum	



Octane Blue

BRAKES	800	1000
Front	Dual 220 mm ventilated disc brakes with hydraulic twin-piston calipers with Dynamic Brake Control (ABS + HHC + HDC)	
Rear	Dual 220 mm ventilated disc brakes with hydraulic twin-piston calipers with Dynamic Brake Control (ABS + HHC + HDC)	

DIMENSIONS / CAPACITIES

Estimated Dry Weight	1,331 lb (603.7 kg)	1,364 lb (618.7 kg)
Chassis / Cage	Profiled cage ROPS approved	
L x W x H	118 x 62 x 69 in. (300.5 x 157.8 x 175.3 cm)	
Wheelbase	90.6 in. (230.1 cm)	
Ground Clearance	10 in. (25.4 cm)	
Cargo Box Capacity	300 lb (136 kg)	
Towing Capacity	1,500 lb (680 kg)	
Storage Capacity	Total: 5.3 gal (20.2 L) Glove Box: 4.1 gal (15.6 L) Driver storage: 0.4 gal (1.5 L) Center console and Cup holders: 0.8 gal (3.1 L)	
Fuel Capacity	10 gal (38 L)	

FEATURES

Gauge	7.6 in. (19.3 cm) wide digital display with keypad Speedometer, tachometer, odometer, trips and hour meters, fuel, gear position, SPORT / ECO™ mode, seat belt and 4 x 4 indicator, front and rear diff lock indicators, diagnostics, clock, battery voltage, engine temperature
Instrumentation	Lighter type DC outlet in console (20-A)
Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™) with Start/ Stop button
Magneto	650-W
Lighting	Two 55 W reflectors and LED tail lights
Winch	N/A
Steering Wheel	Adjustable tilt steering
Protection	Integrated front steel bumper Full skid plate Mudguard and Mudflap
Hitch Type	2 in. Rear hitch receiver and tow ball

WARRANTY

Factory warranty	2-years BRP limited warranty
------------------	------------------------------