Can-am. MAVERICK TRAIL DPS 700 T

HIGHLIGHTS		
AGILE	Sturdy engine and transmission Easy Handling and capabilities Front and rear suspension designed for trail riding	
ADVENTUROUS	Meaningful functionalities and versatilities Enhanced comfort with Ergo-Lok cockpit Build your Maverick Trail that fits your needs	
CONFIDENT	 Can-Am design and proven fit & finish Enhanced protection More adventure and less maintenance 	
PLATFORM FEATURES	• 62.8 in. (159.6 cm) wide • 90.6 in. (230.1 cm) wheelbase • 10 in. (25.4 cm) of ground clearance • Up to 10.5 in. (26.7 cm) suspension travel • 7.6 in. (19.3 cm) wide digital display with keypad • SPORT / ECO™ modes • Net (instead of doors) • RF D.E.S.S. with Start / Stop button • Mudguard and Mudflap • Rear hitch and tow ball • 7-pin trailer connexion (12V) • LED tail lights with halo glow effect • Horn, flashers and position lamps, left/right mirrors, lic plate support, hook on front metal bumper, driver seat detector, low brake fluid sensor • Over 60 km/h top speed	eense
SPECIFIC TO DSP 700 T	Dynamic Power Steering (DPS™) 12 in. (30.5 cm) aluminum wheels	

Ergoprint seats with color accentsDynamic Brake Control

• Dynamic Traction Control (BTC + DTC)

(ABS + HHC + HDC)

PACKAGE

ENGINES

Туре	39 kW (52 hp) / 41 lb-ft, Rotax® ACE (Advanced Combustion Efficiency) 650 cc single cylinder, liquid cooled, with catalytic converter
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	PDrive primary CVT with engine braking and Electronic Drive Belt Protection L / H / N / R / P
Drive Train	Selectable 2WD / 4WD with Open front diff. with Brake Traction Control (BTC)
Driving Assistance	Electronic Hill Descent Control SPORT / ECO™ modes
Power Steering	Dynamic Power Steering (DPS)
SUSPENSIONS	
Front Suspension	Double A-arm with sway bar / 10 in. (25.4 cm) travel
Front Shocks	Twin tube gas charged shocks
Rear Suspension	TTA with sway bar / 10.5 in. (26.7 cm) travel
Rear Shocks	Twin tube gas charged shocks
TIRES / WHEELS	
Front Tires	Carlisle ACT 26 x 8 x 12 in. (66 x 20.3 x 30.5 cm)
Rear Tires	Carlisle ACT 26 x 9 x 12 in. (66 x 22.9 x 30.5 cm)
Wheels	12 in. (30.5 cm) cast-aluminum



BRAKES	
Front	Dual 220 mm disc brakes with hydraulic twin- piston calipers with Dynamic Brake Control (ABS + HHC + HDC)
Rear	Dual 220 mm disc brakes with hydraulic twin- piston calipers with Dynamic Brake Control (ABS + HHC + HDC)


DIMENSIONS / CAPACITIES

Steering Wheel

Protection

Hitch Type

Estimated Dry Weight *	1,271 lb (576.5 kg)
Chassis / Cage	Profiled cage
	ROPS approved
LxWxH	118 x 62.8 x 69 in.
	(300.5 x 159.6 x 175.3 cm)
Wheelbase	90.6 in. (230.1 cm)
Ground Clearance	10 in. (25.4 cm)
Cargo Box Capacity	300 lb (136 kg)
Towing Capacity	1,500 lb (682 kg)
Storage Capacity	Total: 5.3 gal (20.2 L)
	Glove Box: 4.1 gal (15.6 L)
	Driver storage: 0.4 gal (1.5 L)
	Center console and Cup holders: 0.8 gal (3.1 L)
Fuel Capacity	10 gal (38 L)
FEATURES	
Gauge	7.6 in. (19.3 cm) wide digital display with
	keypad, Speedometer, tachometer, odometer, trips and hour meters, fuel, gear position,
	SPORT / ECO™ mode, seat belt and 4 x 4
	indicator, front and rear diff lock indicators,
	diagnostics, clock, battery voltage, engine
	temperature
Instrumentation	Lighter type DC outlet in console (20-A)
Anti-theft System	RF Digitally Encoded Security System
<u>, </u>	(D.E.S.S.™) with Start / Stop button
Magneto	650-W
Lighting	Two 55 W reflectors and LED tail lights with halo glow effect
Winch	N/A







Adjustable tilt steering

Integrated front steel bumper, Full skid plate Mudguard and Mudflap

2 in. hitch receiver with rear hitch and tow ball