

HIGHLIGHTS

- Rotax[®] V-Twin engine
- Arched double A-arm front suspension with front sway bar
- Front and rear FOX† 1.5 PODIUM† RC2 shocks
- Continuously Variable Transmission (CVT) with engine braking
- Tri-Mode Dynamic Power Steering (DPS)
- 12 in. (30.5 cm) cast-aluminum beadlock wheels
- 25 in. (63.5 cm) ITP Holeshot ATR tires
- · Front & central skid plate
- · Aluminum taper-profile handlebar with full wrap handguards
- Surrounding Spar Technology (SST) G2 frame with Geometric Contact Control
- Torsional Trailing arm Independent (TTI) rear suspension
 Anti-Lock Braking System (ABS)
- Multifunction digital gauge
- X-package coloration, graphics and seat cover
 RF Digitally Encoded Security System (D.E.S.S.™)



Chalk Gray & Magma Red

DIMENSIONS / CAPACITIES

ENGINE

Туре	60 kW (80 hp), Rotax® 976 cc V-twin, liquid cooled
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	CVT, P / R / N / H / L, standard engine braking
Drive Train	Selectable 2WD / 4WD with Brake Traction Control (BTC)
Power Steering	Tri-Mode Dynamic Power Steering (DPS)
Speed Category	More than 60 km/h

SUSPENSIONS

Front Suspension	Arched double A-arm with front sway bar 9.2 in. (23.3 cm) travel
Front Shocks	FOX† 1.5 PODIUM† RC2
Rear Suspension	Torsional Trailing arm Independent (TTI) 9.9 in. (25.1 cm) travel
Rear Shocks	FOX† 1.5 PODIUM† RC2

TIRES / WHEELS

Front Tires	ITP Holeshot† ATR 25 x 8 x 12 in. (63.5 x 20.3 x 30.5 cm)
Rear Tires	ITP Holeshot† ATR 25 x 10 x 12 in. (63.5 x 25.4 x 30.5 cm)
Wheels	12 in. (30.5 cm) cast-aluminum beadlock

RRAKES

BRAKES	
Front	Dual 214 mm disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm disc brake with hydraulic twin-piston caliper

Estimated Dry Weight * 710 lb (323 kg) LxWxH 86 x 48 x 49 in. (218.4 x 121.9 x 124 cm) Wheelbase 51 in. (129.5 cm) Ground Clearance 10.5 in. (26.7 cm) Seat Height 34.5 in. (87.7 cm) Rear: 35 lb (16 kg) **Rack Capacity** Storage Capacity N/A 660 kg trailer with brakes and **Towing Capacity** 335 kg trailer without brakes 5.4 gal (20.5 L) **Fuel Capacity** FEATURES 4.5-in. digital display: Gauge Speedometer, tachometer, odometer, trip & hour meters, gear position, 4 x 4 indicator, temperature, engine lights, electronic fuel gauge & clock Lighter type DC Outlet in console, standard Instrumentation connector in the back (15-A) Anti-theft System RF Digitally Encoded Security System (D.E.S.S.™) Lighting 240 W from 4 fender mounted projector beam headlamps (60-W) with tail light / brake light Winch N/A T-Category features Towing hitch with trailer plug, directional indicators, position lamps, mirrors, horn Standard Seat Front bumper Protection Aluminum taper-profile handlebar with full

wrap handguards Front & central skid plate

WARRANTY

Factory warranty

2-year BRP limited warranty

©2021 Bombardier Recreational Products Inc (BRP). All rights reserved, 11, and the BRP logo are trademarks of Bombardier Recreational Products Inc, or its affiliates, In the U.S.A., the products ©2021 Bombardier Recreational Products Inc (BRP). All rights reserved.¹⁴, ¹⁴ and the BRP logo are trademarks of Bombardier Recreational Products Inc. or its affiliates. In the U.S.A., the products are distributed by BRP US Inc. ²Base model dry weight shown. ¹Visco-Lok is a trademark of GKN Viscodrive GmbH. ¹All other trademarks are the property of their respective owners. For other jurisdictions, see your local dealer. Because of our ongoing commitment to product quality and innovation, BRP reserves the right, at any time, to discontinue or change specifications, prices, designs, features, models or equipment without incurring obligation. Ride responsibly. BRP highly recommends that all ATV drivers take a training course. For safety and training information, see your dealer. ATVs can be hazardous to operate. For your safety: the operator and passenger should wear a helmet, eye protection and other protective colting. Always remember that riding and alcohol / drugs dont mix. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90cc are recommended for weight and older. Never earry passengers on any ATV not specifically designated for such use. Passenger must be at least 12 years old and able to hold handgrips and plant feet while seated against the backrest. Some models depicted may include optional equipment.

