## **MY23 OUTLANDER MAX 6X6 XU+ 650 T / 1000 T**



## HIGHLIGHTS

- Selectable 4WD / 6WD
- Tri-Mode Dynamic Power Steering (DPS)
  Continuously Variable Transmission (CVT) with extra low L-gear
- 12 in. (30.5 cm) cast-aluminum wheels
- · 26 in. (66 cm) Carlisle† ACT HD 6-Ply tires
- 3,500-lb (1,588 kg) winch
- Dump dual-level cargo box with modular accessories
- Heated grips and throttle
- Speed limiter
- 1000 only: Painted plastics for premium look

DIMENSIONS / CAPACITIES 650

ENGINE	650	1000	
Туре	44 kW (59 hp), Rotax® 650 cc V-twin, liquid cooled	60 kW (80 hp), Rotax® 976 cc V-twin, liquid cooled	
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)		
Transmission	CVT, P / R / N / H / Extra Low L, Intelligent Engine Braking (iEB™)		
Drive Train	Selectable 4WD / 6WD with Visco-Lok† QE auto-locking front differential		
Power Steering	Tri-Mode Dynamic Pow	Tri-Mode Dynamic Power Steering (DPS)	
Speed Category	Up to 60 km/h	Up to 60 km/h	
SUSPENSIONS			
Front Suspension	Arched double A-arm v 9.2 in. (23.3 cm) travel	Arched double A-arm with front sway bar 9.2 in. (23.3 cm) travel	
Front Shocks	Oil		
Rear Suspension	Double Torsional Trailing arm Independent (TTI2) with quick-release sway bar 9.9 in. (25.1 cm) travel		
Rear Shocks	Oil		
TIRES / WHEELS			
Front Tires	Carlisle† ACT HD 26 x 8 (66 x 20.3 x 30.5 cm)	Carlisle† ACT HD 26 x 8 x 12 in. (66 x 20.3 x 30.5 cm)	
Rear Tires	Carlisle† ACT HD 26 x 10 x 12 in. (66 x 25.4 x 30.5 cm)		
Wheels	12 in. (30.5 cm) cast-aluminum		
BRAKES			
Front	Dual 214 mm disc brak twin-piston calipers	Dual 214 mm disc brakes with hydraulic twin-piston calipers	
Rear	Dual 214 mm disc brak twin-piston calipers	Dual 214 mm disc brakes with hydraulic twin-piston calipers	

DIMETORIO CON CONTROLLES	000	1000
Estimated Dry Weight *	595 kg	597 kg
LxWxH	317 x 123 x 140 cm	
Wheelbase	228.5 cm	
Ground Clearance	27.9 cm	
Seat Height	87.7 cm	
Rack Capacity	Front: 45 kg / Rear: 318 kg	
Storage Capacity	Dual-level cargo box with sidewalls and tailgate Rear: 18.5 gal (70 L)	
Towing Capacity	907 kg trailer with brakes 674 kg trailer without brakes	
Fuel Capacity	5.4 gal (20.5 L)	
FEATURES		
Gauge	4.5 in. digital display	
Instrumentation	DC Outlet, 15-A connector	
Ingnition	RF Digitally Encoded Security System (D.E.S.S.™)	
Lighting	LED headlights	
Winch	3,500-lb (1,588 kg) winch	
T-Category features	Towing hitch with trailer plug, directional indicators, position lamps, mirrors, horn	
Seat	Reinforced seat skin Convertible Rack System (CRS)	
Handlebar	Standard with heated grips & throttle	
Protection	Heavy-Duty front bumper	
WARRANTY		
Factory warranty	2-year BRP limited warranty	

1000



