MY24 OUTLANDER X MR 700



PACKAGE HIGHLIGHTS

- Snorkeled CVT intake and exhaust
- · Relocated radiator

Factory Warranty

- Tri-Mode Dynamic Power Steering (DPS)
- Work / Standard / Sport modes
- Visco-4Lok † front differential
- 28 in. (71.1 cm) XPS Swamp King tires 14 in. (35.6 cm) aluminum wheels
- Front Bumper, Full skid plate, X mr footpegs
- Premium Glovebox with cellphone holder and USB charger

ENGINE	700
Туре	37 k W (50 hp) / 41 lb-ft, Rotax® ACE (Advanced Combustion Efficiency) 650 cc, single cylinder, liquid cooled with strategically positioned engine air intake
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	pDrive primary CVT with strategically positioned air intake and exhaust Extra low L/H/N/R/P
Drive Train	Selectable 2WD / 4WD / Lock 4WD with Visco-4Lok† front differential
Driving Assistance	Work / Standard / Sport modes
Power Steering	Tri-Mode Dynamic Power Steering (DPS)
Speed Category	Over 60 km/h
SUSPENSIONS	
Front Suspension	Double A-arm 9 in. (22.9 cm) travel
Front Shocks	Twin tube
Rear Suspension	Double A-arm 9.75 in. (24.8 cm) travel
Rear Shocks	Twin tube
TIRES & WHEELS	
Front & Rear Tires	XPS Swamp King 28 x 8/10 x 14 in. (71.1 x 20.3 / 25.4 x 35.6 cm)
Wheels	14 in. (35.6 cm) aluminum
BRAKES	
Front	Dual 214 mm disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm disc brake with hydraulic twin-piston caliper

Estimated Dry Weight*	876 lb (397.3 kg)
LxWxH	89.9 x 48.8 x 48.2 in. (228.4 x 123.9 x 122.5 cm)
Wheelbase	53 in. (134.5 cm)
Ground Clearance	13 in. (33 cm)
Seat Height	38.6 in. (98 cm)
Rack Capacity	Front: 120 lb (54.4 kg) / Rear: 240 lb (109 kg)
Storage Capacity	9 gal (34 L)
Taurina Canasitu	1,830 lb (830 kg) trailer with brake
Towing Capacity	870 lb (394 kg) without brakes
Fuel Capacity FEATURES Gauge	870 lb (394 kg) without brakes
Fuel Capacity FEATURES	870 lb (394 kg) without brakes 5.1 gal (19.5 L)
Fuel Capacity FEATURES Gauge	870 lb (394 kg) without brakes 5.1 gal (19.5 L) 4.5 in. digital display
Fuel Capacity FEATURES Gauge Instrumentation	870 lb (394 kg) without brakes 5.1 gal (19.5 L) 4.5 in. digital display USB phone charger RF Digitally Encoded Security System (D.E.S.S.™)
Fuel Capacity FEATURES Gauge Instrumentation Ignition	870 lb (394 kg) without brakes 5.1 gal (19.5 L) 4.5 in. digital display USB phone charger RF Digitally Encoded Security System (D.E.S.S.™) with cord
Fuel Capacity FEATURES Gauge Instrumentation Ignition Lighting	870 lb (394 kg) without brakes 5.1 gal (19.5 L) 4.5 in. digital display USB phone charger RF Digitally Encoded Security System (D.E.S.S.™) with cord LED headlights and taillights
Fuel Capacity FEATURES Gauge Instrumentation Ignition Lighting Winch	870 lb (394 kg) without brakes 5.1 gal (19.5 L) 4.5 in. digital display USB phone charger RF Digitally Encoded Security System (D.E.S.S.™) with cord LED headlights and taillights N/A

2-year BRP limited warranty





